

Product comparison



LR-2.ST the High-Performer

PRICE
On Request

Ident. No. 0020013291



LR-2.ST the Versatile

PRICE
On Request

Ident. No. 0020013293



LR-2.ST the Compact Power

PRICE
On Request

Ident. No. 0020013294

Useable volume min.	500 ml	500 ml	500 ml
Useable volume max.	2000 ml	2000 ml	2000 ml
Working temperature min.	room temp. °C	room temp. °C	room temp. °C
Working temperature max.	230 °C	230 °C	230 °C
Attainable vacuum	25 mbar	25 mbar	25 mbar
Viscosity max.	150000 mPas	70000 mPas	50000 mPas
Speed min.	8 rpm	8 rpm	8 rpm
Speed max.	290 rpm	290 rpm	290 rpm
Telescope stand stroke	390 mm	390 mm	390 mm
Material in contact with medium	borosilicate glass, FFPM, PTFE, steel 1.4571	borosilicate glass, FFPM, PTFE, steel 1.4571	borosilicate glass, FFPM, PTFE, steel 1.4571
Reactor vessel openings (units/standard)	3/NS 29/32 2/NS 14/23	3/NS 29/32 2/NS 14/23	3/NS 29/32 2/NS 14/23
Width	460 mm	460 mm	460 mm
Depth	430 mm	430 mm	430 mm
Height	1240 mm	1240 mm	1240 mm
Weight	25 kg	34 kg	25 kg
Permissible ambient temperature min.	5 °C	5 °C	5 °C
Permissible ambient temperature max.	40 °C	40 °C	40 °C
Permissible relative humidity	80 %	80 %	80 %

Subject to technical changes